

1200L IBC with UN / DN150, EPDM gasket, G2 plug with venting
DN50 Screw Ball Valve/Butterfly Valve, EPDM gasket/
2 label plates/Steel frame pallet

Jiangsu Jieyuan

Date: 2023

第 1 页, 共 2 页

**技术数据 (Technical data):**

公称容积 (Nominal Capacity)	1260 升 (Liter)
满口容积 (Brimful Capacity)	1200 升 (Liter)
长度 (Length)	1200 毫米 (mm)
宽度 (Width)	1000 毫米 (mm)
带托盘高度 (Height with pallet)	1350 毫米 (mm)
灌装口直径 (Filling opening)	150 毫米 (mm)
放料口直径 (Discharge opening)	50 毫米 (mm)
叉车开口 (Fork opening)	100 毫米 (mm)
标记板 (Label plate)	1 块 (piece)
护角 (Corner Protector)	4 块 (piece)
重量 (Weight) 内容器 (Inner container) (含盖子阀门)	17.5 (kg) \pm 0.5
总重量 (Total Weight) 约 (approx)	62 千克 \pm 2 (kg)

技术数据可能被修改, 所有的尺寸均为近似值。 (Technical subjects to change, all dimensions approximately)

1200L IBC with UN / DN150, EPDM gasket, G2 plug with venting/	Jiangsu Jieyuan
DN50 Screw Ball Valve/Butterfly Valve, EPDM gasket/	Date:2023
2 label plates/Steel frame pallet	第 2 页, 共 2 页

Construction:	
Outer Container: Rectangular grid box made of tubular Steel material, with bottom plate, connected on top with tie-bar (assembled with brackets), label plate with manual on front side, additional Label plate on the back side.	
Material: Grid / Bottom plate:	Steel, galvanized
Corner Protector:	4 pieces made of PE-HD
Inner Container: Rectangular blow molded tank of high density polyethylene, with filling opening in the middle of the top section.Discharge opening at the bottom of the front side. Contain anti-aging and anti-UV plastic particles	
Material:	PE-HD, natural
Filling Opening: DN150 with external thread, closed with screw cap, G2-plug with vent, sealing-cap and gasket.	
Material:	Screw cap DN150: PE-HD, red
	O-ring gasket: EPDM
	G2-plug: PP
	O-ring of 2 inch gasket: EBA, natural
	Vent: Silastic
Discharge	DN50 Screw Ball Valve/Butterfly Valve with yellow/blue handle and provide with safety ring. Outlet sealed with an PE-lined Al-film,secured with clip.
Opening:	Valve closed with screw cap, PE-disk and flat-gasket. Outlet nozzle enclosed.
Material:	Ball Valve/Butterfly valve: PE-HD, White
	Flap-gasket: EPDM
	Spherical gasket ETFE
	Screw cap DN50: PE-HD, black
	Flat-gasket screw cap: PE,form
	PE-disk: PE-HD, red
	Outlet nozzle: PE-HD, natural
Pallet:	Steel-frame pallet (1000 x 1200 mm), 4-way entry
Notice plate:	Label plate with manual on front side, additional label plate on the back side.
	Front Size:500*380mm/Back Size:470*380mm
Material:	Steel, galvanized
Heavy metals:	Concentration level of heavy metals (Pb, Cd, Cr VI and Hg) in packaging does not exceed 100ppm
Delivery:	Ready for filling
UN-marking:	UN 31 HA1
技术数据可能被修改, 所有的尺寸均为近似值。(Technical subjects to change, all dimensions approximately)	